




Plugs

MZS 4



Product	MZS 4
description	Injection-moulded adapter plug from 4 mm diameter plug to 2 mm diameter socket. This adapter plug enables the use of 2 mm system plugs and 4 mm system measuring leads.
operating instruction	BA416
article-no. / *colour	9735991xx <div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;">  00 black </div> <div style="text-align: center;">  01 red </div> </div> <div style="text-align: right; border: 1px solid black; padding: 2px; margin-top: 10px;">Ni</div>
drawing	 <p style="text-align: center;">Buchse für 2mm Stecker socket for 2 mm plug</p>
technical data	
connection	spring loaded socket 2 mm
rated voltage ⁽¹⁾	30 VAC / 60 VDC
measurement cat. acc. to IEC 61010	O ⁽³⁾
rated current ⁽¹⁾ (consider derating curve)	6 A
material plug	brass, nickel plated
housing material	PP
temperature range acc. To IEC61010 ⁽²⁾	-20 °C to +60 °C
flammability class acc. to UL 94 (only valid for basic material of housing)	HB
standard	IEC 61010

4 mm system

⁽¹⁾ for normal environmental conditions -5°C to +40°C

⁽²⁾ contact the manufacturer for applications at deviating temperature ranges

⁽³⁾ without rated measurement category, for other circuits that are not directly connected to mains
stand: 19.06.2019